




Tiny LED Module




The TMT LEDs Silver Series Tiny LED module is designed for channel letter with a narrow stroke width. With its small footprint, the Tiny module fits in strokes as narrow as 0.5" with clear light dispersion. It features the same CrystaLens optics and has a 170° x 130° wide viewing angle that expands its coverage evenly across the face requiring fewer modules per letter than other comparable products in the market.

Features

- ✓37-41 lumens per module
- ✓IP 67 rated
- ✓Very small footprint 0.8 cm x 1.5 cm
- ✓Good for narrow applications (as small as 1,2 cm)
- ✓Up to 115 lumens per watt
- ✓Color options available
- ✓Ideal for 2.5 cm - 7.5 cm Deep applications

Applications

- ✓Ideal for channel letter
- ✓Ideal for any application requiring small footprint





TMT Elektronik Sistemleri
Sanayi A.Ş.
info@tmtleds.com
www.tmtleds.com

Datasheet Game Player TDS-Tiny



Operating Temperature	-30°C ~ +60°C	Lead Wire	Tin Coated Copper Wire
Storage Temperature	-30°C ~ +60°C	Lifetime TM21	>60.000 Hours
Body Material	Case: ABS Optics: Optical PC	Adhesive Tape	3M Foam
Finishing	Ultrasonic Welding	Strip Size	100 Modules/Strip

CONSTANT VOLTAGE 12V DC 5 SDCM 130° x 170° BEAM ANGLE

	Tiny White Options	Tiny Color Options					
Power	0.36W	0.36W					
Current	30 mA	30 mA					
Modules per Foot	6	6					
60W Power Supply Load	166 Total / 25 Single	166 Total / 25 Single					
	Color	Order Code	Lumens	Lm/W	Order Code	Lumens	Lm/W
	10.000K	101171	41	115	RED	101170	11 31
	6.500K	101169	41	115	GREEN	102490	6 17
	4.000K	101168	38	105	BLUE	101172	15 42
	3.000K	101057	38	105			

Packaging Details

Chain **Bag** **Box**
100 pcs 100 pcs 6.000 pcs

Can Depth (cm) ■ Optimal ■ Acceptable

Density Guideline **1"** **2"** **3"** **4"** **5"** **6"** **7"** **8"** **9"** **10+"**

TINY ■ ■ ■ ■

Luminous flux tolerance ±10% - CCT tolerance ±8%

